Web <u>Images Maps News Shopping Gmail more</u> •

Sign in



drop doorbell buffer register queue

Search | A

Advanced Search Preferences

Web

Results 1 - 10 of about 1,200 for drop doorbell buffer register queue. (0.36 seconds)

Tip: Save time by hitting the return key instead of clicking on "search"

1.22001/10/02 23:05:14 \* linux/include/linux/cyclades.h \* \* This ... struct CUSTOM\_REG { uclong fpga\_id; /\* FPGA Identification Register \*/ uclong .... Tx buffer \*/ #define C\_CM\_Q\_ENABLE 0x58 /\* enables queue access from the ... cvs.sourceforge.jp/cgi-bin/viewcvs.cgi/uclinux-h8/uClinux-2.0.x/include/linux/cyclades.h? rev=1.1.1.1 - 26k - Qached - Similar pages

#### Re: [ofa-general] post recv question | KernelTrap

36 posts - Last post: Feb 21, 2008

When you post to a receive queue, the buffer does not belong the ... post\_recv code rings a doorbell (write to adapter mem or register) t3: ...

https://kerneltrap.org/mailarchive/openfabrics-general/2008/2/21/939994/thread - 102k - Cached - Similar pages

#### Re: [ofa-general] post\_recv question | KernelTrap

... hw work queue t2: post\_recv code rings a doorbell (write to adapter mem or register) t3: post\_recv returns t4: <app assumes the buffer is ready&gt; ...

https://kerneltrap.org/mailarchive/openfabrics-general/2008/2/21/939554/thread - 102k - Cached - Similar pages

More results from https://kerneltrap.org »

#### Source Code, Sample Code or Example Code For writel

sa\_writel(dev, Mailbox4, 0); /\* \* Clear the synch command doorbell to start on a .....

vb.queue); q->curr = buf; DEB INT(("next buffer: buf:%p, prev:%p, ...

www.codase.com/search/call?name=writel - 67k - Cached - Similar pages

#### [PDF] InfiniBand Support in Xen Virtual Machine Environment

File Format: PDF/Adobe Acrobat - View as HTML

HCA and register a callback handler with CQ. Completion queue can also be accessed through .... buffer and ringing the doorbell to notify the ...

ftp://ftp.cse.ohio-state.edu/pub/tech-report/2005/TR63.pdf - Similar pages

#### BSDCon '03 — Technical Paper

In addition to context switch overhead, the memory buffer used to stage data to and from ... unit doorbell or queue pointer register is written is critical. ...

www.usenix.org/events/bsdcon03/tech/full\_papers/thorpe/thorpe\_html/index.html - 146k - Cached - Similar pages

## GIT e4f775874f071120204c58a21eafe132ca5f2396 master.kernel.org ...

+\*/++/\* disable the RAM Buffer receive queue \*/+ sky2\_write8(hw, RB\_ADDR( rxqaddr [port], RB\_CTRL), RB\_DIS\_OP\_MD); ++ for (i = 0; i < 0xffff; ...

www.kernel.org/pub/linux/kernel/people/akpm/patches/2.6/2.6.14-rc1/2.6.14-rc1-mm1/broken.../git-netdev-all.patch - 234k - Cached - Similar pages

### IPDFI MPC8540 PowerQUICC III™ Integrated Host Processor Reference Manual

File Format: PDF/Adobe Acrobat

Doorbell Queue Enqueue Pointer Address Register (DQEPAR) . ...

www.freescale.com/files/32bit/doc/ref\_manual/MPC8540RM.pdf - Similar pages

#### [РРТ] Efficient User-Level Networking in Java

File Format: Microsoft Powerpoint - View as HTML

send/recv ticket ring. send/recv. queue. descriptor. buffer .... public ViJbufTicket register(Vi vi); /\* reg + pin jbuf \*/ ...

www.cs.comell.edu/Info/People/chichao/talk-final.ppt - Similar pages

# (WO/2004/093378) AN APPARATUS AND METHOD FOR ALLOCATING RESOURCES ...

Although described as a "register," the data to be stored in doorbell register 620 .... As illustrated, a set of output queues 860 may temporarily buffer the ... www.wipo.int/pctdb/en/wo.jsp?WO=2004093378&IA=US2004010912&DISPLAY=DESC -

143k - Cached - Similar pages

1 ;	2	3	4	<u>5</u>	<u>6</u>	<u>7</u>	8	<u>9 10</u>	Next
-----	---	---	---	----------	----------	----------	---	-------------	------

drop doorbell buffer register queue Search

Search within results | Language Tools | Search Tips | Dissatisfied? Help us improve |
Try Google Experimental

Google Home - Advertising Programs - Business Solutions - Privacy - About Google